



Spesifikasi :

V _{IN}	Input Frequency	A _{IN}	P ₁ Input Power	I ₂ Current range	V _o	DUTY CYCLE	Rated Output Voltage
Input Voltage AC380 V±15% 3PH	50/60	23.1 A	15.1 KVA	20-100 A	293 V	60%	120 V
Efficiency 85%	Power Factor 0.93	Cutting Thickness ≤ 40 MM	Arc-Initiating Untouch	Air Pressure (MPa) 0.4-0.5 MPa	IP Protection Class IP21	Weight 36.5 kg	Dimensions (mm) 550x280x545 (mm)

Aksesoris Standar :



P80 5m



300A+16mm²x3m



Regulator



Hose Clamp

Features :

1. Arc-Striking halus dengan HF Control.
2. Kualitas pemotongan dan travel speed yang luar biasa.
3. Perlengkapan cutting dengan harga dan kualitas terbaik.
4. Ketebalan yang direkomendasikan: 30mm (Carbon Steel)
5. Pilot-Arc untuk menghemat bahan kerja.
6. Jangkauan luas untuk voltase input: 380V± 15%.
7. Hemat energi



Application :

- Perawatan dan pemeliharaan
- Dekorasi
- Konstruksi
- Pengolahan baja atau stainless stel
- Pabrik kecil dan menengah